

TrueMud™

Dynamic Shearing / Mixing + Heating Technology

- TrueMud is a low pressure, patent pending, dynamic shear mixing + heating technology that improves ROP with more effective control of ECD especially when drilling narrow mud weight pressure sensitive formations.
- TrueMud Dynamic Shear completely activates drilling mud chemistries by better hydrating polymers and making stronger emulsions
- Excellent hole cleaning and suspension without “over treating” chemical additives
- Hydrates shear sensitive polymers without “fisheyes” and without degrading them
- In HTHP testing - cuts filtrate losses in half and the water in the filtrate by an order of magnitude

Proven Shear Mixing with TrueMud Technology

- Over 100,000 bbls reliably mixed for critical offshore jobs
 - Out-performed rotor/stator shear mixing
 - Safer mixing at only 80 PSI max pressure compared to 1500+ psi shear mixing
- Fully-developed, known rheology without a trip through the bit
- Increases Yield Point by 2x without increasing plastic viscosity
- Stable, consistent mud - requires less intervention
- Enhanced performance of Solids Control Equipment with 120°F or greater exit temperatures
- Saves on chemical loading costs

Dynamic Shear Mixing Makes Better Mud!


Test Temp. °F	Before Shear		After Shear Dynamic	
	Ambient	@120°F	Ambient	@120°F
14.1 PPG New Mud				
Electric Stability, ES	326		816	
Plastic Viscosity, PV	35	30	48	28
Yield Point, YP	11	4	22	13
Gels	5/7/7	4/5/5	15/17/19	9/10/10
11.7 PPG Mud				
Electric Stability, ES		163		316
Plastic Viscosity, PV	38	26	37	28
Yield Point, YP	27	12	34	22



Improved Electrical Stability & Rheology Oil/Water/Surfactant Emulsion Magnified to 1000X


Conventional Mixing w/o Shear

- Not a completely homogenous blend
- Potential for early separation in static fluids
- You can't predict performance until it goes through the bit at least one time!



TrueMud Dynamic Shear + Heat

- 2x even 3x the measured electrical stability
- Prevents separation in static fluids
- TrueMud Properties and Stability without a trip through the bit!



TrueMud Dynamic Shear Mixing + Heating

- Patent pending, yet proven technology
- Centrifugal force from a spinning disc creates controlled cavitation inside of closed-end boreholes
- Cavitation bubbles create dynamic shear and heating within the fluid
- An elegant, robust, reliable, repairable, oilfield-tough, low pressure device
- Multiple power options, diesel or electric drives
- Shear results from cavitation bubbles in the fluid - not by mechanical means
- Flameless, scale-free heating up to 300°F



TrueMud Shear Mixer Configurations



TrueMud Shear Mixer
"Drop-In" Unit on a 8
by 10 Foot Skid.



TrueMud Shear Mixer "Self-Contained" in a 20' Box on Location



Laboratory Size TrueMud Shear Mixer

TrueMud™
Dynamic Mixing / Shearing / Heating Technology
Makes Better Mud

For more information:



281-397-6278

11221 Cutten Road, Bldg 5 • Houston, TX 77066
k.smith@highlandfluid.com • www.highlandfluid.com